



PROFESSIONAL LINE



Honing & Polishing

UNIVERSAL GLOSSY

Universal polishing cream for natural stone and agglomerates

UNIVERSAL GLOSSY is a water-based polishing cream for polishing surfaces made of natural stone. **UNIVERSAL GLOSSY** is ideal for polishing mixed floors made of marble, limestone, travertine, granite, quartz, and agglomerates. The product provides a glossy finish characterized by excellent resistance to pedestrian traffic.

- BENEFITS**
- ✓ Versatile solution
 - ✓ High shine
 - ✓ Superficial closure to dirt
 - ✓ Water-based product

USES This product is suitable for use on indoor and outdoor use on Marble, Granite, Travertine, Limestone, Agglomerates, Quartz

COVERAGE 50/70 m²/kg

APPLICATION EQUIPMENT Single disc machine with at least 2.0 HP; manual polishing machine. Faber Chimica can supply the WARRIOR single disc machine, which has a power of 2.2 HP and is optimized for the correct application of any product.

- APPLICATION STEPS**
- Surface preparation**
- Carefully clean the surface, making sure to remove any dust or dirt present. We suggest using our **DETERFUG** or our **FABER 30**, depending on the nature of the dirt and the surface type.
 - We suggest applying the product on surface sections of 0,5 m² at a time.
 - Apply the product to surfaces with a temperature of between +5 and +40°C
 - Any adjacent surfaces not being treated with the product must be protected.

Application

Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.

- **UNIVERSAL GLOSSY** is a white solid paste. It can be brought to a creamier state by shaking the container. The different consistencies of the product do not affect its effectiveness and performance. If applied to its solid paste consistency by buffing it with a single disk machine it will become creamier.
- Shake it well before the application and then place 2/3 tea spoons of product on the surface, it will be enough to cover m²
- Immediately after placing the product on the surface start buffing the product with a single-disk machine equipped with a white pad with rpm 150-200. Buff the product in circular motions making sure to apply the product evenly throughout the whole section. As you apply the product we recommend broadening the movement towards the next section.
- Apply the product to the following sections as described above.
- Once the surface has been polished remove the dry residues using a cloth, a broom or a vacuum-cleaner.

MADE IN ITALY

100%



PROFESSIONAL LINE

APPLICATION STEPS

To achieve a higher shine or superficial closure we recommend to repeat the application. Generally 2-3 product application can be done per section. The product doesn't give layering defects.

When restoring the shine on particularly worn out surfaces we recommend applying the product 2-3 times per section.

When in need to maintain the shine we recommend doing 1-2 applications per section.

Resuming the surface use

After carefully removing any residues and rinsing the surface with water, the floor can be opened for use.

MAINTENANCE PRODUCTS

- For the daily maintenance of a surface treated with **UNIVERSAL GLOSSY**, we recommend: **ALGAFLOOR** or **NEUGEL** depending on the type of material
- For heavy-duty cleaning of a surface treated with **UNIVERSAL GLOSSY**, we recommend **FABER 30** or **DETERFUG**, according to the type of dirt and the material to be cleaned.

INSTRUCTIONS AND GUIDELINES

- Never apply the product to a wet surface
- Do not apply the product to overly heated surfaces
- Apply the product to surfaces with a temperature of between +5 and +40°C
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using water.

PHYSICAL-TECHNICAL DATA

Formula	Cream
Color	Light blue
Odor	Unscented
pH:	2,7 ± 0,5

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

1 kg Bucket – 12 buckets per box
5 kg Bucket – 4 buckets per box

SAFETY

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

Revisione 3.0 – 23/10/2024

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.